



Vexve X - Choose the right handle for your needs!

You can choose the basic handle or T-handle for X-series shut-off valves according to your operating needs. The new handles allow a better insulation distance to ensure energy efficiency. The handles are made of composite, which is a lightweight, durable and more environmentally friendly material choice than metal. You can remove the handles without tools.

Properties:

- · Material composite / PA+GF*
- · Handle torque duration 60 Nm
- · Maximum short-term operating temperature 220 °C

*The composite material used in the handles has been subjected to aging tests, which have also included temperature fluctuations and exposure to UV radiation. According to the test results, the X-series handle is even better suited for outdoor use than the galvanized steel handle.

Available:


- · Suitable for X series DN 10-50 shut-off valves
- · The same handle is suitable for all DN sizes



Stem extension

The insulation dimension can be increased by 50 mm with the help of a stem extension. The stem extension is also stackable (e.g. two stem extensions, 100 mm insulation dimension increase).


| Product | Product number | | |
|------------------------|----------------|--|--|
| Vexve X stem extension | 901162 | | |



Handle

The basic handle is delivered standard with X-series shut-off valves. When ordered separately delivered standard with a blue Vexve lid. Other colour variations are also available.

| Product | Product number | | |
|----------------|----------------|--|--|
| Vexve X handle | 901115X | | |




100 032X

| DN | А | D1 | D2 | D3 | Н | H1 | L |
|----|-----|------|------|----|-----|----|-----|
| 10 | 130 | 17.2 | 33.7 | 32 | 119 | 86 | 230 |
| 15 | 130 | 21.3 | 33.7 | 32 | 119 | 86 | 230 |
| 20 | 130 | 26.9 | 42.4 | 32 | 123 | 87 | 230 |
| 25 | 130 | 33.7 | 48.3 | 32 | 125 | 86 | 230 |
| 32 | 130 | 42.4 | 60.3 | 32 | 129 | 85 | 260 |
| 40 | 130 | 48.3 | 70.0 | 32 | 133 | 87 | 260 |
| 50 | 130 | 60.3 | 76.1 | 32 | 140 | 88 | 260 |

T-handle

The T-handle, which can be ordered separately, is ideal for situations where the operating space is limited. Recommended sizes DN 10–32. Comes standard with a blue Vexve lid. Other colour variations are also available.

| Product | Product number | | |
|-------------------------------|----------------|--|--|
| Vexve X T-handle, blue lid | 901116X | | |
| Vexve X T-handle, red lid | 901116X/R | | |



| 100 032X |
|----------|
|----------|

| DN | А | D1 | D2 | D3 | Н | H1 | L |
|----|----|------|------|----|-----|----|-----|
| 10 | 90 | 17.2 | 33.7 | 31 | 105 | 63 | 230 |
| 15 | 90 | 21.3 | 33.7 | 31 | 105 | 63 | 230 |
| 20 | 90 | 26.9 | 42.4 | 31 | 109 | 64 | 230 |
| 25 | 90 | 33.7 | 48.3 | 31 | 111 | 63 | 260 |
| 32 | 90 | 42.4 | 60.3 | 31 | 115 | 63 | 260 |
| 40 | 90 | 48.3 | 70.0 | 31 | 120 | 64 | 260 |
| 50 | 90 | 60.3 | 76.1 | 31 | 127 | 65 | 260 |



Vexve Oy

Pajakatu 11 38200 Sastamala Finland